

NIPOCLAD PRIMER

Liquid-Applied Polymer Primer

DESCRIPTION

NipoClad Primer is a water-based environmentally-friendly liquid applied acrylic polymer primer.

It promotes adhesion between the substrate and the subsequent acrylic based waterproofing membrane or wall coating.

RECOMMENDED USES

For the priming of:

- Old and new concrete
- Metal roofs
- Old clay roof tiles
- Refurbishment of old roofs
- Vertical wall

ADVANTAGES

- Water-based, non-toxic
- Act as a bonding agent to old substrates
- Seal pores on rough porous concrete to prevent air bubbles
- Easy to apply

APPLICATION

Surface Preparation

Ensure surface is clean from dust, oil, rust, grease, loose materials, moss etc. Surface should be dry for homogeneous material quality.

New concrete must be cured for at least 28 days.

NipoClad Primer can be applied using brush, roller or spray applied.

Whilst every effort is made to ensure that the contents of this material is accurate and current, it is the user's responsibility to satisfy itself of the suitability of products for its own particular purpose. As the actual use by others is beyond our control, we do not provide any guarantee, implied or expressed, as to the effects of such use. No liability is accepted by Nipo International Pte Ltd, its staff and/or its distributors, for any loss or damage, direct or indirect, that may result from using the product, information or adopting recommendations and/or suggestions as actual conditions for use are beyond our control. This information is not to be construed as absolutely complete since additional information may be necessary or desirable for exceptional or particular circumstances. Dated July 2020

Prime

Apply one coat of *NipoClad Primer* to the substrate. A second coat may be necessary if the surface is porous.

Allow the priming coat to dry.

Once *NipoClad Primer* is touch-dry, apply subsequent coats of *NipoClad Acrylic* or *Nipo ThermoShield*.

COVERAGE

Approximately 0.2L of *NipoClad Primer* can cover about 1m² per coat.

PACKING

NipoClad Primer comes in 20L pail and 200L drum.

NOTES

Actual Measurement may vary due to the condition of the substrate. This information is only a guide.

TYPICAL PROPERTIES

Appearance	White milky liquid
Resistance to Light	Good
Resistance to Ageing	Good
Flash Point	Non Flammable

Imported and Exclusively marketed in India by

Nohara Trading & Services India Pvt. Ltd.

CIN: U74900DL2016FTC290800

F-6 (Basement), Lajpat Nagar III, New Delhi 110024, India

Email: info@nohara.in



www.nohara.in